

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: H01Q 1/24	A1	(11) International Publication Number: WO 99/60660 (43) International Publication Date: 25 November 1999 (25.11.99)
(21) International Application Number: PCT/US99/09118 (22) International Filing Date: 27 April 1999 (27.04.99) (30) Priority Data: 09/080,074 15 May 1998 (15.05.98) US (71) Applicant: ERICSSON INC. [US/US]; 7001 Development Drive, Research Triangle Park, NC 27709 (US). (72) Inventors: SADLER, Robert, A.; 1507-515 Woodway Club Drive, Durham, NC 27713 (US). HAYES, Gerard, J.; 207 Abercrombie Road, Wake Forest, NC 27587 (US). SADLER, John, T.; 2108 Wake Forest Road, Raleigh, NC 27608 (US). (74) Agent: MONCO, Dean, A.; Wood, Phillips, VanSanten, Clark & Mortimer, Suite 3800, 500 West Madison Street, Chicago, IL 60661-2511 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW. ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: FLIP OPEN ANTENNA FOR A PORTABLE TELEPHONE		
(57) Abstract <p>An antenna for a communication device including a first flip (14) having an antenna element and pivotally mounted on a housing (12) to move from a closed position adjacent to the housing to an operational position angularly spaced from the housing. A second flip (16) having a conductive element as a ground plane is pivotally mounted on the housing and moves between a closed position adjacent the housing and an open position angularly spaced from both the housing and the first flip. When the first and second flips are in the closed position, they cover the controls and no antenna is exposed on the exterior of the housing. In the operational position, the antenna element and the conductive element form an antenna optimally tuned to the frequency of the wireless network that is less subject to interference by the user.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
B	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

WO 99/60660

PCT/US99/09118

FLIP OPEN ANTENNA FOR A PORTABLE TELEPHONE

FIELD OF THE INVENTION

This invention relates to antennas for communication devices.

BACKGROUND OF THE INVENTION

5 Antennas for hand-held communication devices (also called mobile phones, cell phones and mobile stations) are commonly either fixed or telescoping. Each of these antennas has its advantages and disadvantages. A fixed antenna is, by definition, at the optimal length for its operating frequency. Fixed antennas, however, do not store compactly, and hence the antenna is always vulnerable to
10 damage. Telescoping antennas, on the other hand, are protected inside the communication device when not in use. Telescoping antennas, however, can be difficult to open and users are less likely to fully extend the antenna, adversely affecting antenna performance. Particularly when not properly stored, telescoping antennas are more fragile than fixed antennas.

15 Furthermore, both types of antennas for hand-held communication devices are subject to interference from the user. The user's body absorbs and reflects radio waves in patterns that are difficult to predict when the antenna is designed. Thus, an antenna designed for optimal performance on a given frequency may not perform optimally when actually used by a particular person.

20 Therefore, it is an object of this invention to provide an antenna that is not subject to bending and breaking, whether in use or stored.

It is a further object of this invention to provide an antenna that can be tuned precisely for the operating frequency of its wireless network.

It is a further object of this invention to provide an antenna that can minimize
25 interference caused by the human body.

SUMMARY OF THE INVENTION

These and other objects and advantages are achieved by our flip antenna for a communication device. Our flip antenna comprises a first piece or "flip" having an

antenna element. The first flip is pivotably mounted on the communication device housing to move between a closed position adjacent to the housing and an operational position angularly spaced from the housing. A second flip having a conductive surface opposite to the antenna element provides a ground reference for the antenna element. The second flip is pivotably mounted on the housing, between the housing and the first flip, to move between a closed position adjacent the housing and an operational position angularly spaced from both the housing and the first flip.

In the operational position, the angle between the first and second flips provides optimal tuning for the operating frequency of the communication device. Advantageously, in the operational position the angle between the first and second flips is tunable so that the parasitic capacitance matches a second resonance to create a dual-band single impedance antenna. Further, the conductive surface on the second flip is between the antenna element and the user, which shields the antenna from interference caused by the human body. In the closed position, the first flip covers the housing and the second flip, so that there is no exposed antenna.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the invention may be obtained from consideration of the following description, taken in conjunction with the drawings, in which:

Fig. 1 is a perspective view of a communication device utilizing a flip antenna according to an exemplary embodiment of this invention;

Fig. 2 is a side view of the communication device of Fig. 1 illustrating a closed position of the flip antenna and housing;

Fig. 3 is a side view of the communication device of Fig. 1 illustrating an operational position of the flip antenna;

Fig. 4 is a perspective view of the first flip of the flip antenna;

Fig. 5 is a perspective view of the second flip of the flip antenna; and

Fig. 6 is a perspective view of the housing of the communication device of

Fig.1.**DETAILED DESCRIPTION**

Fig.1 is a perspective view of a hand-held communication device according to an exemplary embodiment of our invention, shown generally at 10. Communication device 10 comprises a housing 12, a first flip 14 and a second flip 16. Housing 12 includes operational controls for communication device 10. Such controls include keypad 18 and function buttons 20, 22 and 24 (send, end and clear), as known in the art. Optional side mounted control 26 performs functions such as volume control and/or power on-off. A display 28 provides information to the user regarding the current state of communication device 10. Housing 12 also includes microphone 30.

First flip 14 includes an antenna element 32. Second flip 16 includes a speaker 34 and a conductive element 36. Fig.1 illustrates communication device 10 in the operational position. In this exemplary embodiment, speaker 34 is part of second flip 16 to maintain the spacing between microphone 30 and speaker 34 at a comfortable distance for the user. Speaker 34 may optionally be on housing 12, above display 28. Engagement tab 38 on first flip 14 engages engagement tab 40 on second flip 16 to pull second flip 16 up from its closed position into an operational position when first flip 14 is moved into the operational position.

Fig.2 is an illustration of communication device 10 in its closed position. In the closed position, first flip 14 covers the operational controls on housing 12. As seen in this illustration, there is no exposed antenna. Thus, there is nothing to break or bend. The only exposed control is volume/on-off switch 26.

Turning now to Fig.3, a side view of communication device 10 is shown in its operational position. First flip 14 is angularly spaced from housing 12. Controls such as function button 24 and keypad 18 are now accessible. Furthermore, microphone 30 and speaker 34 are in a usable position. Engagement tab 38 has moved engagement tab 40 to move second flip 16 into the operational position.

In this operational position, the plane 42 antenna 32 and the plane 44 of

conductiv I ment 36 ar spaced fr m each other by an angl α . This angl is set at the factory for optimal operation of the antenna for the frequency or frequencies that communication device 10 will operate on. Conductive element 36 generally comprises a ground plane for antenna element 32. Additionally, conductive element 5 36 shields the antenna from the effects of the human body. To further improve the performance of antenna element 32, metal plating or foil forming an additional ground plane 46 (shown in phantom) may be included in the interior of the top portion of housing 12, as is currently practiced in the art.

Antenna element 32 generally comprises a half wave or quarter wave 10 antenna. When antenna element 32 is the length of a quarter wave, angle α between antenna element 32 and conductive element 36 is more important to proper functioning of the antenna than when antenna element 32 is a half wave. Advantageously, when antenna element 32 is a half wave, the angle α may be adjusted so that the impedance of the antenna matches a second resonance to 15 create a single input, dual band antenna, which configuration is useful in a dual mode communication device (*i.e.*, when the communication device operates in both 800 and 1900 Mhz frequencies).

Fig.4 is an illustration of a first flip 14 according to this exemplary embodiment. First flip 14 includes the antenna element 32. Antenna element 32 is 20 illustrated as metal strip secured to the surface 50 that faces the housing 12 when the first flip 14 is closed. Alternatively, antenna element 32 may be a metal patch or trace, or some other form of conductive material. Further, antenna element 32 may be wire secured to the surface of first flip 14 or molded into the flip.

First flip 14 includes integral side portions 52 and 54. Side portions 52 and 25 54 include holes 56 and 58, respectively, to facilitate mounting on an axle to form a hinge. Side portion 54 also includes first engagement tab 38. Engagement tab 38 engages a further engagement tab 40 on second flip 16 (as will be shown below) in order to lift second flip 16 while first flip 14 is being open and moved to the operational position.

Modular plug 62 engages a plug on the back of housing 12 (not shown) to connect antenna element 32 electrically to the communications circuitry in housing 12. Alternatively, wires or another connection device may replace modular plug 62. Optionally, there may be additional antenna traces 64 and 66. Traces 64 and 66
5 provide an additional ground plane or provide a second antenna element for multiband operation.

Turning to Fig. 5, second flip 16 is illustrated. Second flip 16 includes a conductive element 36 on one side. As described above, conductive element 36 provides a ground plane for an antenna and provides shielding between the antenna
10 and the user according to this exemplary embodiment. Conductive element 36 comprises metal foil in this illustration, but may also comprise a piece of metal or other conductive material. Additionally, conductive element 36 may be molded into second flip 16.

Second flip 16 includes hinges 70 and 72 with holes 74 and 76, respectively,
15 for mounting second flip 16 on the same axle as first flip 14. Second flip 16 fits inside side plates 52 and 54 of first flip 14. A second engagement tab 40 on second flip 16 engages first engagement tab 38 of first flip 14 moving second flip 16 from a closed position adjacent to housing 12 to an open, operational position when first flip 14 is itself pivoted to its operational position (shown in Fig. 3). Alternatively,
20 second flip 16 may be biased towards the operational position by a spring, which pivots second flip 16 into the operational position when first flip 14 is manually pivoted to the operational position. A speaker 34 (shown in phantom) is optionally mounted on second flip 16. Alternatively, speaker 34 may be molded into second flip 16.

25 In Fig.6, housing 12 is illustrated with the first and second flips 14, 16 removed. Housing 12 includes a mounting portion 80 on its top side with an axle 82 protruding from either side. First flip 14 and second flip 16 are pivotally mounted on axle 82. Axle 82 may be biased outwardly by internal springs so that they can be compressed for installation and removal of first and second flips 14, 16. Mounting

WO 99/60660

PCT/US99/09118

6

portion 80 also includes a stop 84 that engages second flip 16 to stop it in its operational position. Adjusting the position of stop 84 adjusts the angle between the first and second flips.

5 It is to be understood that the above-described embodiment is an illustration of our invention and that many variations may be devised by those skilled in the art without departing from the scope of this invention. For example, an antenna according to our invention can be used with hand-held two-way radios. Therefore, this invention is limited only by the following claims.

CLAIMS:

1. An antenna for a hand-held communication device having a housing,
said antenna comprising:
a first flip pivotally mounted on said housing for movement between a closed
5 position adjacent to said housing and an operational position spaced from said
housing, said first flip having an antenna element; and
a second flip pivotally mounted on said housing and moving from a closed
position adjacent said housing and an operational position angularly spaced from
both said housing and said first flip, said second flip having a conductive element
10 opposite said antenna element forming a ground plane for said antenna.
2. An antenna in accordance with claim 1 wherein said first and second
flip each have a top portion and a bottom portion, said antenna further comprising
a first hinge on the bottom portion of said first flip and a second hinge on said
bottom portion of said second flip, wherein both said first and second hinges guide
15 said flips for rotation about an axis passing through said housing.
3. An antenna in accordance with claim 2 further comprising a first
engagement tab on said first hinge engaging said second flip to rotate said second
flip from said closed position to said operational position when said first flip is moved
from said closed position to said operational position.
- 20 4. An antenna in accordance with claim 3 further comprising a stop on
said housing to stop said second flip at said open position.
5. An antenna in accordance with claim 4 wherein said antenna
comprises a single input dual-band antenna.
6. An antenna in accordance with claim 1 wherein said second flip

WO 99/60660

PCT/US99/09118

8

incorporates a speaker.

7. An antenna in accordance with claim 1 wherein said antenna element comprises a conductive trace.

8. An antenna in accordance with claim 1 wherein said antenna element
5 comprises a strip of metal.

9. An antenna in accordance with claim 8 wherein said first flip is molded,
and wherein said conductive strip is molded into said first flip.

10. A communication device comprising:
a housing having a front with operating controls and an end having an axle;
a first flip having an integrated antenna element pivotable on said axle from
a closed position covering the front of said first portion to an operational position;
5 and
a second flip having a conductive element opposed to said antenna element
pivotable on said axle between a closed position between said housing and said first
flip and an operational position at an angle from said first flip, wherein said antenna
element and said conductive element form an antenna for said communication
10 device.
11. A communication device in accordance with claim 10 further
comprising a first engagement tab on said first flip engaging said second flip to
rotate said second flip to its operational position when said first flip is moved to its
operational position.
- 15 12. A communication device in accordance with claim 11 further including
a stop on said housing to stop said second flip at its operational position as said first
flip is moved to said operational position.
13. A communication device in accordance with claim 10 wherein said
second flip includes a speaker.

WO 99/60660



PCT/US99/09118

10

14. A communication device comprising:
an operational unit including user controls, a microphone and a radio
communications device; and
an antenna including
- 5 a cover pivotally mounted on said operational unit and including an
antenna element, said cover pivoting from a closed position adjacent to said
user controls and protecting said antenna element to an operational position
angularly spaced from said user controls exposing said antenna element, and
an intermediary conductive element pivoting on said hinge from a
- 10 closed position between said cover and said user controls to an operational
position at a defined angle with said cover in said operational position.
15. A communication device in accordance with claim 14 wherein said
intermediary conductive element includes a speaker.



WO 99/60660

PCT/US99/09118

Fig. 1*Fig. 2*

WO 99/60660

PCT/US99/09118



WO 99/60660

PCT/US99/09118





Fig. 6



INTERNATIONAL SEARCH REPORT

Int'l Application No

PCT/US 99/09118

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H01Q1/24

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H01Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 170 173 A (KRENZ ERIC L ET AL) 8 December 1992 (1992-12-08) column 1, line 62 - column 2, line 25; figure 1	1-15
Y	DE 44 22 644 A (KERN RALF M) 11 May 1995 (1995-05-11) column 2, line 25 - column 3, line 12; figure 3	1-15
Y	EP 0 661 825 A (NIPPON ELECTRIC CO) 5 July 1995 (1995-07-05) column 4, line 11 - column 4, line 32; figures 4,5	6,13,15
	-/-	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"A" document member of the same patent family

Date of the actual completion of the international search

10 August 1999

Date of mailing of the international search report

18/08/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5618 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Cannard, J-M

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 99/09118

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No. .
A	EP 0 323 614 A (MOTOROLA INC) 12 July 1989 (1989-07-12) column 3, line 46 - column 6, line 8; figures 1,2	1,10,14
A	GB 2 280 322 A (NIPPON ELECTRIC CO) 25 January 1995 (1995-01-25) page 4, line 14 - page 5, line 4; figure 1	6,13,15
A	US 5 561 436 A (PHILLIPS JAMES P) 1 October 1996 (1996-10-01) column 2, line 41 - column 3, line 24; figures 1,2	1,10,14
A	FR 2 702 324 A (PICO GICA SA) 9 September 1994 (1994-09-09) page 5, line 4 - page 5, line 16; figure 6	1,10,14
A	US 5 752 204 A (CHENNAKESHU SANDEEP ET AL) 12 May 1998 (1998-05-12) column 7, line 24 - column 8, line 30; figures 3,5	1,10,14
A	US 5 726 383 A (GELLER URI ET AL) 10 March 1998 (1998-03-10) column 3, line 7 - column 4, line 19; figure 2	1,10,14

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/09118

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5170173 A	08-12-1992	CA 2109919 C DE 4391937 C DE 4391937 T FR 2691843 A GB 2271887 A,B IT 1262357 B JP 6508019 T MX 9302411 A WO 9322803 A	23-07-1996 18-07-1996 05-05-1994 03-12-1993 27-04-1994 19-06-1996 08-09-1994 01-10-1993 11-11-1993
DE 4422644 A	11-05-1995	DE 9421222 U DE 9421593 U	14-09-1995 15-05-1996
EP 0661825 A	05-07-1995	JP 2689881 B JP 7203524 A FI 946098 A US 5630211 A	10-12-1997 04-08-1995 29-06-1995 13-05-1997
EP 0323614 A	12-07-1989	US 5014346 A AT 123358 T CA 1302502 A DE 3853909 D DE 3853909 T EP 0643436 A HK 99497 A JP 1198121 A JP 2602083 B MX 168716 B	07-05-1991 15-06-1995 02-06-1992 06-07-1995 04-01-1996 15-03-1995 08-08-1997 09-08-1989 23-04-1997 04-06-1993
GB 2280322 A	25-01-1995	JP 2576367 B JP 7038461 A JP 2821346 B JP 7074807 A AU 682871 B AU 6861694 A FI 943471 A GB 2319416 A,B GB 2319417 A,B US 5905966 A	29-01-1997 07-02-1995 05-11-1998 17-03-1995 23-10-1997 02-02-1995 24-01-1995 20-05-1998 20-05-1998 18-05-1999
US 5561436 A	01-10-1996	BR 9502395 A CA 2153541 A,C CN 1122056 A DE 19526581 A FR 2722919 A GB 2292258 A,B JP 8056109 A SG 52158 A US 5572223 A	25-06-1996 22-01-1996 08-05-1996 01-02-1996 26-01-1996 14-02-1996 27-02-1996 28-09-1998 05-11-1996
FR 2702324 A	09-09-1994	NONE	
US 5752204 A	12-05-1998	AU 2432797 A CA 2250245 A EP 0891642 A WO 9737398 A	22-10-1997 09-10-1997 20-01-1999 09-10-1997
US 5726383 A	10-03-1998	AU 2402497 A	19-11-1997

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/09118

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5726383 A		DE 29723581 U	27-05-1999
		EP 0846407 A	10-06-1998
		WO 9741717 A	06-11-1997